

Product datasheet

Specifications



APC Back-UPS Connect 12Vdc 36W, lithium-ion, mini network ups to protect internet routers, IP cameras and more

CP12036LI

Main

| | |
|---------------------------|----------------------|
| Main Input Voltage | 12 V DC 1 phase |
| Product or component type | Power supply |
| Main Output Voltage | 12 V DC 1 phase |
| Battery type | Li-Ion (Lithium-Ion) |
| Range of product | Back-UPS Connect |

Complementary

| | |
|----------------------|---------|
| Number of tare power | 2 W |
| Mounting mode | Plug-in |

Batteries & Runtime

| | |
|-----------------------|-----|
| Battery recharge time | 9 h |
|-----------------------|-----|

Physical

| | |
|----------------|--------------------|
| Colour | White |
| Width | 99 mm |
| Depth | 109 mm |
| Product weight | 0.3 kg |
| Mounting mode | Not rack-mountable |
| Height | 25 mm |

Output

| | |
|---------------------------------|------|
| Maximum configurable power in W | 36 W |
| Output voltage | 12 V |

Conformance

| | |
|------------------------|--|
| Product certifications | CE |
| Standards | CE EN/IEC 61000-4-8 EN/IEC 61000-4-2 EN/IEC 62368-1 |

Environmental

| | |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...40 °C |
|---------------------------------------|-----------|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|-------------------------------------|--------------|
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -10...50 °C |
| Storage altitude | 0...5000 m |
| IP degree of protection | < IP20 |

Packing Units

| | |
|------------------------------|----------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.300 cm |
| Package 1 Width | 11.500 cm |
| Package 1 Length | 16.300 cm |
| Package 1 Weight | 366.000 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 3.900 kg |
| SCC14 | 10731304632396 |
| Pallet unit layers | 6 |
| Pallet layers | 4 |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 186 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 172 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.6 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.3 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 11 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 2 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | 73b1309a-d65b-4414-9fb4-d80a65253bd6 |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|-------------------------------|---|
| Recyclability potential, in % | 33 |
| Removable battery | Yes |
| Take-back | No |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative





