

Product datasheet

Specifications



Battery Breaker Kit, 630A, one circuit breaker for Easy UPS 3M/3L

E3MBBK100K200H

Overview

Presentation Battery breaker kit that controls DC voltage sent from third party battery solutions to the UPS.

Main

Product or component type Kit
Battery type VRLA
Provided equipment Installation guide

Batteries & Runtime

Number of battery free slots 0
Number of battery filled slots 0
Device mounting Enclosed battery cabinet
Battery power in VAh 0 VAh

Physical

Height 53 cm
Width 32 cm
Depth 23 cm
Product weight 13 kg
Mounting mode Not rack-mountable

Environmental

Ambient air temperature for operation 0...40 °C
Operating altitude 0...4921 ft
Relative humidity 0...95 % non-condensing

Packing Units

Unit Type of Package 1 PCE
Number of Units in Package 1 1
Package 1 Height 80 cm
Package 1 Width 57 cm
Package 1 Length 50 cm
Package 1 Weight 29 kg

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins