

Product datasheet

Specifications



Easy UPS 3M 60kVA 400V 3:3 UPS for external batteries, Start-up 5x8

E3MUPS60KHS

Overview

Presentation

Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 60 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. It is supplied without batteries, so you can easily customize your battery solution. Includes 5x8 start-up service.

Main

Main Input Voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Input voltage	380 V 415 V
Maximum input current	104 A
Max short time withstand current	10 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.5 leading to 0.5 lagging
Cos phi	0.99
Input voltage limits	342...477 V
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Network frequency	40...70 Hz
Output voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Output voltage	380 V 415 V
Rated power in W	60 kW
rated power in VA	60 kVA
Bypass type	Built-in static bypass
Crest factor	3 : 1
Harmonic distortion	Less than 3 %
Maximum configurable power in VA	60 kVA
Maximum configurable power in W	60 kW
Output harmonic distortion	< 3% linear load and < 5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
UPS type	Double conversion online

Wave type	Sine wave
Output frequency	50 Hz sync to mains 60 Hz sync to mains

Complementary

Battery type	Lead-acid external sold separately
Control panel	Touch screen LCD user interface
Free slots	1
UPS connectivity	Pre-installed network management card 3
Colour	White (RAL 9003)
Height	91.5 cm
Width	36 cm
Depth	85 cm
Product weight	109 kg
USB compatible	Yes
Provided equipment	Dust filter Installation guide Start-up service
Range of product	Easy UPS 3M
Product or component type	Uninterruptible power supply (UPS)

Environment

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...55 °C
Storage altitude	0...15240 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	65 dBA
Heat dissipation	10523 Btu/h
Operating altitude	0...4921 ft

Batteries & Runtime

Battery type	External battery system
--------------	-------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	114.000 cm
Package 1 Width	47.500 cm
Package 1 Length	96.500 cm
Package 1 Weight	133.000 kg

Contractual warranty

Warranty (in months)

12



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	70 606 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	70 605 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	Bcc48c21-81f4-41e7-bf2b-336ef659ee43
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


Recyclability potential, in %	76
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

