

Product datasheet

Specifications



Battery Breaker Kit 630A, EL, for Galaxy VS/VL/VXL and Easy UPS 3-Phase Modular, and Easy UPS 3M Advanced

GVBBK630EL

Overview

Presentation Battery breaker kit that controls DC voltage sent from third party battery solutions to the UPS. For use with empty classic battery cabinets or third party battery solutions deployed with Galaxy VS/VL, Easy UPS 3-Phase Modular, and Easy UPS 3M Advanced uninterruptible power supplies.

Main

Product or component type	Kit
Range of product	Galaxy VS
Range compatibility	Galaxy VS
Battery type	VRLA Li-Ion (Lithium-Ion)

Physical

Height	52 cm
Width	29 cm
Depth	24 cm
Product weight	12 kg

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-25...55 °C
Storage Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	536 mm
Package 1 Width	800 mm
Package 1 Length	500 mm
Package 1 Weight	25 kg

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No