

Product datasheet

Specifications



APC Smart-UPS On-Line, 5kVA/
5kW, Rack/Tower, 230V, 2x IEC
C13+1x IEC C19+Hard wire 3-wire
(H+N+E) outlets, Network Card,
W/O rail kit

SRTG5KXLI

Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V 240 V
Maximum input current	30 A
Switching current capacity	40 A
Input voltage limits	160...285 V full load 100...285 V half load
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Network frequency	40...70 Hz auto-sensing
Output voltage	230 V AC 1 phase
Output voltage	220 V 240 V
Rated power in W	5000 W
Rated power in VA	5000 VA
Output connection type	2 IEC 60320 C13 1 IEC 60320 C19
Output connector type	Hard wire 3-wire (1P + N + E) for 1 zone(s)
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	5000 VA
Maximum configurable power in W	5000 W
UPS type	On-Line
Wave type	Sine wave
Efficiency	93.5 %
Output frequency	50/60 Hz +/- 4 Hz sync to mains

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery type	Lead-acid internal included
Emergency power off	Yes
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Pre-installed network management card 3
Surge energy rate	600 J
Number of rack unit	4U
Colour	Black (RAL 9005)
Height	175 mm
Width	440 mm
Depth	620 mm
Product weight	55.9 kg
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal
Mounting mode	Rack-mounted with included kit
Provided equipment	1 x USB cable 1 x RJ45 cable 1 x rack mounting brackets 1 x stabilization/wall mounting feet 1 x installation manual 1 x C13-C14 power cord
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Smart-UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE UKCA TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing

Storage Relative Humidity	0...95 % non-condensing
Acoustic level	55 dBA
Heat dissipation	1108.95 Btu/h
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	+/- 96 V
Extended runtime	1
Number of battery filled slots	2
Number of battery free slots	0
Battery recharge time	4 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Battery charger power	239 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.500 cm
Package 1 Width	79.000 cm
Package 1 Length	59.000 cm
Package 1 Weight	68.700 kg
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Height	70.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	143.400 kg

Contractual warranty

Warranty (in months)	24 Battery 36 UPS
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	17 553 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	433 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	21 kg CO2 eq.
Carbon footprint of the installation phase [A5]	14 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	65 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	A64c500c-f72a-458b-8faa-8175a94429fe
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


Recyclability potential, in %	31
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



