

# Product datasheet

Specifications



## APC Easy UPS On-Line, 3kVA/ 2700W, Tower, 230V, 6x IEC C13 + 1x IEC C19 outlets, Intelligent Card Slot, LCD

SRV3KI-E

EAN Code: 0731304436874

## Overview

**Presentation** High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

## Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V 240 V
Input Connection Type	IEC 60320 C20
Input voltage limits	110...285 V 40% load 180...285 V full load
Network frequency	40...70 Hz auto sensing
Output voltage	230 V AC 1 phase
Output voltage	220 V 240 V
Rated power in W	2700 W
rated power in VA	3000 VA
Output connection type	6 IEC 60320 C13 1 IEC 60320 C19
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	3 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
UPS type	On-Line
Wave type	Sine wave
Efficiency	88 % (full load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	<a href="#">APCRBCV205</a>

## Graphs

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>

## Complementary

<b>Additional information</b>	Configurable for 220 : 230 or 240 nominal output voltage
<b>Battery type</b>	Lead-acid internal included
<b>Control panel</b>	Multifunction LCD status and control console
<b>Free slots</b>	1
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>UPS connectivity</b>	Serial port USB port Available expansion slot
<b>Surge energy rate</b>	945 J
<b>Cable length</b>	1.5 m
<b>Number of cables</b>	1
<b>Colour</b>	Black (RAL 7010)
<b>Height</b>	336 mm
<b>Width</b>	190 mm
<b>Depth</b>	425 mm
<b>Product weight</b>	26.0 kg
<b>Mounting location</b>	Front
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Vertical
<b>Mounting mode</b>	Tower
<b>Max runtime</b>	3 min
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No
<b>Range of product</b>	Easy UPS On-Line
<b>Product or component type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product certifications</b>	CE UKCA TISI
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-20...50 °C
<b>Storage altitude</b>	0...15000 m
<b>IP degree of protection</b>	IP20
<b>Relative humidity</b>	0...95 % non-condensing
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Acoustic level</b>	50 dBA

---

Heat dissipation	1024 Btu/h
------------------	------------

---

Operating altitude	0...3000 m
--------------------	------------

---

## Batteries & Runtime

---

Battery type	Lead-acid battery
--------------	-------------------

---

Battery voltage	72 V
-----------------	------

---

Extended runtime	0
------------------	---

---

Number of battery filled slots	0
--------------------------------	---

---

Number of battery free slots	0
------------------------------	---

---

Battery recharge time	4 h
-----------------------	-----

---

Battery life	3...5 year(s)
--------------	---------------

---

Battery charger power	60 W rated
-----------------------	------------

---

Battery power in VAH	528 VAh runtime
----------------------	-----------------

---

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	46.5 cm
------------------	---------

---

Package 1 Width	56.5 cm
-----------------	---------

---

Package 1 Length	32.5 cm
------------------	---------

---

Package 1 Weight	28 kg
------------------	-------

---

## Logistical informations

---

Country of origin	CN
-------------------	----

---

## Contractual warranty

---

Warranty (in months)	24
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	1 910 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	597 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	7 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 302 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	58
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

