

Product datasheet

Specifications



APC Easy UPS On-Line SRV 72V RM Battery Pack for 2/3 kVA Extended Runtime Model



SRV72RLBP-9A

Main

Product or component type	External battery pack
Number of rack unit	2U
Battery type	Lead-acid battery
Provided equipment	User manual Battery cable Rack mounting brackets
Range of product	Easy UPS On-Line

Batteries & Runtime

Number of battery blocks per string	6
Device mounting	Rack mount
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	72 V

Physical

Colour	Black
Height	86 mm
Width	438 mm
Depth	632 mm
Product weight	42.5 kg
Mounting mode	Rack-mounted with kit
USB compatible	No

Conformance

Product certifications	CE UKCA EAC EN/IEC 62040-1
------------------------	-------------------------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Storage Relative Humidity	0...95 % non-condensing
----------------------------------	-------------------------

Storage altitude	0...15000 m
-------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	24 cm
-------------------------	-------

Package 1 Width	80 cm
------------------------	-------

Package 1 Length	60 cm
-------------------------	-------

Package 1 Weight	53.1 kg
-------------------------	---------

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	243 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	196 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	13 kg CO2 eq.
Carbon footprint of the installation phase [A5]	15 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	185 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	19 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

